When specifying fixing options below, indicate shaft size and type, i.e: screw fix (SF), push fix (D), splined (SPL) or collet.

SHAFT SIZE	3mm	4mm	4mm	4mm	6mm	6mm	6mm U.S.A.	6mm	6mm	1/4 inch	1/4 inch	1/4 inch	1/4 inch	MARKER
KNOB TYPE	•					5.0	4.5							DOT & LINE OPTIONS
K1C					•				•	•		•		S (std)
K4C									Ø			•		Z
K5, K8					•				•	•		•		Z, S
K6C, K6C/SKT				•		Ø			•			•		D SL N
K7C					•	Ø			•	•		•		Z
K85, K88		•			•	•	•			•	•			Z (std)
K86R							•							LZ
K87MA, K87MB [†]		Ø			•	•	•			•				LZ
K9 *	•		•	•	•	•	•	•	•	•		•	•	LDZ
K10 *	•		•	•	•	•	•	•	•	•		•	•	LDZ
K11	•		•	•	•	•	•	•	•	•		•	•	LDZ
K12	•		•	•	•	•	•	•	•	•		•	•	LDZ
K14				•	•		K14P		•	•		•		Z
K15, K15P				•	•				•	•		•		K15 - Z
K16, K16P				•	•		K16P		•	•		•		K16 - Z
K17									Ø	Ø		•		Z (std)
K18					•				•			•		
K19					•									D
K21				•	•	•			•	•		•		ΖD
C18, C18/SKT					•	•	•			•				C18 - Z(std) C18/SKT SL N
KM12B, KM15B					•									
KM20B, KM40B, KM50B					•		Ø							
KMK SERIES					•		•							
KMR SERIES					•		Ø			KMR40D				
KEY	COLLET		SPLINED		D-SPRING		SCREW		• = AVAILABLE - STD Ø = ENQUIRE IF REQD.					L - Body line D - Cap dot S - Skirt dot Z - Cap line SL - Skirt line N - Numbered

^{*} For All Black model only - version with integral cap is available. NOT ALL PUSH FIX MODELS HAVE METAL SPRINGS.

⁺ Including `R' `Soft Touch' versions.