



**DATAMYTE™**

**PRODUCT**



# **LIGHTSTAR™ EV TORQUE WRENCH**

**Insulated for Electric Vehicle and Battery Assembly Applications**

- Precise torque measurement for production and quality control
- Patented insulated design and angle restart algorithm for accuracy
- Ensure safety in potentially hazardous electrical work environments



# **DRILCO**



## LIGHTSTAR™ EV TORQUE WRENCH

The high-growth EV market has spurred demand for tools that both collect data in a potentially hazardous electrical work environment and protect an operator from electric shock and injuries.

Most torque wrench manufacturers offer a non-conductive enclosure for existing tool models – an approach that is not very reliable and can compromise safety of tool operators.

The body components of the DataMyte LightStar EV Torque Wrench are comprised of only non-conductive materials. This insulation delivers reliable, consistent and long-lasting protection against electrical shock and injuries.

### WIRELESS WRENCH SIZES AND SPECIFICATIONS

10 Nm			
25 Nm			
Drive Size (SQ)		1/4"	3/8"
Weight		.9 lb (430 g)	.9 lb (430 g)
Head Width		1.0" (25mm)	1.0" (25mm)
Head Height		.9" (22mm)	.9" (22mm)
Head Height w/Drive		1.3" (32mm)	1.4" (36mm)
Head Length		1.8" (45mm)	1.8" (45mm)
Overall Width		2.0" (50mm)	2.0" (50mm)
Overall Length		11.3" (286mm)	11.3" (286mm)
Pull Length		7.0" (178mm)	7.0" (178mm)
Min/Max Range	Nm	1-10 Nm	2.5-25 Nm
	ft-lb	.74 - 7.38 ft-lb	1.84 - 18.44 ft-lb

Torque Accuracy: 0.25% FSR (Full Scale Range)

#### RATING AND STANDARD COMPLIANCE

- Insulated 1,000 AC volt and 1,500 DC volt rated
- Meets ASTM F1505, EN/IEC 60900

#### NON-CONDUCTIVE BODY MATERIALS

- Torque head
- Transition ring
- Cover plate
- Power button assembly
- Torque handle assembly
- End cap
- External fasteners

#### SAFETY AND DURABILITY TESTING

- Dielectric test – Insulated Torque wrench assembly has been tested to 10,000V - both AC and DC
- Durability and deflection tests - 96000 cycles at 100% load, 10000 cycles at 150% load and the wrench still being within calibration and functional.
- Withstands robust impact testing



**DATAMYTE™**  
Experts in the Connected Factory

2800 Campus Drive, Suite 60, Plymouth, MN 55441  
800-455-4359 | [www.datamyte.com](http://www.datamyte.com) | [info@datamyte.com](mailto:info@datamyte.com)  
UEN3211122

**DRILCO**

Avenida de Somosierra, 22E - 6 y 7  
E-28703 S.S. de los Reyes (Madrid)  
Tel. +34 916 591 900 · [www.drilco.net](http://www.drilco.net)