


Digital Torque & Angle wrenches

with wireless communication





- From 1 N.m to 2000 N.m we have the right tool to assemble or test your product.
- Accuracy of +/- 0.5% F.S and +/- 1% of actual value, to meet stringent requirements.
- Large OLED screen & Buzzer to enable precise torque control.
- Ergonomic, robust, reliable, the perfect tool for your production line.
- Smart and easy to use. Simple setup and operation.
- Designed for Industry 4.0 with the wireless communication options for data traceability.
- Up to 180 hrs with a standard battery.



Use PCFE software with USB connection to:



- Collect results & export to excel
- Backup & restore
- Activate Calibration mode





Bluetooth Solutions

- Set-up Torque operations
- Provide user guidance
- Collect the data in Real-time

Option 1: Integrate the BMS protocol to your software & system.

Option 2: Connect to BMS Custom-Torque software application for iOS and Android



Tool compliance made simple

Self check of calibration date and total torque applications provides alerts for Validation and Calibration requirements.





DRILCO

Core Features	Auditor	Super
Tightening strategies		
Torque control	✓	✓
Torque control / Angle Monitoring	✓	
Quality strategy		
Torque at angle	✓	
Free modes		
Track mode	✓	✓
Peak mode	✓	✓
Memory		
Pset / Tightening setups	99	
Results storage	10,000	
Calibration Self-check by Usage & Date	✓	✓
Human interface		
Large OLED screen	✓	✓
Buzzer	✓	✓
Vibration feedback	Optional	
Data Collection		
USB with PCFE Software	✓	✓
Bluetooth LE	Optional	

Required					
TW	100	Α			
Tool type	Max Torque	Model			
TW = Digital Torque Wrench	Nm	S=Super A=Auditor			

ВТ	EF
Wireless	Extra feedback
Two-way Bluetooth	EF' Vibrating feedback

Examples;

- TW100ABT: Torque & Angle wrench with Bluetooth
- TW100S-EF: Torque wrench with vibration
- TW100ABT-EF: Torque & Angle wrench with Bluetooth & vibration

Units: Nm, ozf.in, lbf.in, lbf.ft, kgf.cm, kgf.m

Languages: English, German, French, Spanish, Italian,

Russian, Polish, Portuguese, Chinese

Power & Communications

Standard wrenches are supplied with 4 * AA batteries. USB cable & PC software included with product.

2 * Lithium-ion cells are required where an EF wrench is selected. These are not included with the product.

Lithium-ion charger: BCH-LI

2 * Lithium-ion BLT-18650



Digital Torque wrenches		Specifications			
Auditor	Super	N.m	Ratchet	Length	Weight
	<u> </u>	(Dri	(Drive)	(mm)	(Kg)
TW010A	TW010S	1 - 10	1/4" or 3/8"		
TW020A	TW020S	2 - 20	(9X12)	410	
TW050A	TW050S	5 - 50	3/8"		0.85
TW100A	TW100S	10 - 100	(9X12)		
TW135A	TW135S	13.5 - 135	(9/12)		
TW200A	TW200S	20 - 200	1/2"	625	1.0
TW340A	TW340S	34 - 340	(14X18)		1.3
TW600A	TW600S	60 - 600	3/4" (24X32)	1360	6
TW800A	TW800S	80 - 800	3/4" or 1"	1360	6
TW1000A	TW1000S	100 - 1000	(24X32)		0
TW1500A	TW1500S	150 - 1500	1"	1600	0
TW2000A	TW2000S	200 - 2000	(27X36)		8

